



DEREX 2630-22 DRILLING RIG

FOR WATER WELL, GEOTHERMAL AND RC EXPLORATION

FEATURES AND SPECIFICATIONS

Truck

Peterbilt 567
Paccar 13 Litre.
Allison 6 speed automatic
Air ride

Transfer Case

Namco (oilfield quality)
Safe Shift

Hydraulic System

Sundstrand, Bosch Rexroth plus gear pump

Top Head

Variable torque and RPM with 2" thru-hole
0-160 rpm @ 0-8000 lbf torque

Derrick & Feed System

26' top head stroke
30,000 -70,000 lbs pullback
20,000 lbs pulldown
120 FPM

Main Winch

12,000 lb.
Hydraulic 135° jib
2,500 lb.
Remote on helpers side for winch

Control Panel

Straight hydraulic controls (no electrics to fail)
Marine grade electric switches (for lights)
Murphy engine monitor display
Twin platforms

Levelling Jacks

Four 36" stroke independently controlled

Night Lights

6 LED night lights

Tool Boxes

30"x 18" x 18"

Overall Dimensions

Length: 38"
Width: 8' 6"
Derrick up height: 42'
Derrick down height: 13' 4"

Water Injection

9 gpm FMC injection pump

Gross Weight

44,000 -46,000lbs

OPTIONS

Sand Line Winch

1,500' sand line

Mud Pump

3x2x13 centrifugal 300 gpm/300 psi
Centerline piston 150 gpm/600 psi

Line Oiler

Many oilers available

Water Injection

18 gpm FMC injection pump

Offsyder Rod Handling System

Drill pipe packages

Wire feeder and box

Hydraulic or gas welders



1018 7th street S.W.
High River, AB, T1V 1A9
Canada
1 (403) 652-8778
sales@derex.ca
www.derex.ca