



DEREX 2630-22 ARTHUR DRILLING RIG

FOR WATER WELL, GEOTHERMAL AND RC EXPLORATION

FEATURES AND SPECIFICATIONS

Truck

Peterbilt 567
Paccar 13 Litre.
Allison 6 speed automatic
Air ride

Transfer Case

Namco (oilfield quality) Safe Shift

Hydraulic System

Sundstrand, Bosch Rexroth plus gear pump

Top Head

Variable torque and RPM with 2" thru-hole 0-160 rpm @ 0-8000 lbf torque

Derrick & Feed System

26' top head stroke 30,000 -70,000 lbs pullback 20,000 lbs pulldown 120 FPM

Air Compressor

Vanair/ Sullair 750 cfm / 350 psi @ 1,800 rpm and 1050 cfm / 350 psi @ 2,200 rpm.

Main Winch

12,000 lb. Hydraulic 135° jib 2,500 lb.

Remote on helpers side for winch

Control Panel

Straight hydraulic controls (no electrics to fail)
Marine grade electric switches (for lights)
Murphy engine monitor display
Twin platforms

Levelling Jacks

Four 36" stroke independently controlled

Night Lights

6 LED night lights

Tool Boxes

30"x 18" x 18"

Overall Dimensions

Length: 38" Width: 8' 6" Derrick up height: 42' Derrick down height: 13' 4"

Water Injection

9 gpm FMC injection pump

Gross Weight

44,000 -46,000lbs

OPTIONS

Sand Line Winch

1,500' sand line

Mud Pump

3x2x13 centrifugal 300 gpm/300 psi Centerline piston 150 gpm/600 psi

Line Oiler

Many oilers available

Water Injection
18 gpm FMC injection pump

Offsyder Rod Handling System

Drill pipe packages

Wire feeder and box

Which recati and box

Hydraulic or gas welders



1018 7th street S.W. High River, AB, T1V 1A9 Canada 1 (403) 652-8778 sales@derex.ca www.derex.ca