

SPECIFICATIONS

Truck

Peterbilt 567 Paccar 13 Litre. Allison 6 speed automatic Air ride

Transfer Case

Namco (oilfield quality) Safe Shift

Hydraulic System

Bosch Rexroth plus gear pump

Top Head

Variable torque and RPM with 2" thru-hole 0-125 rpm @ 3,500 lbf

Lower drive

Variable torque and RPM with 10" thru-hole 0-23 rpm @ 20,000 lbf

Diverter

Simple seal design with 4" NPT discharge to control cuttings.

Derrick & Feed System

13' top head stroke 40,000 lbs pullback 20,000 lbs pulldown 100 FPM

OPTIONS

Sand Line Winch

1,500' sand line

Mud Pump

3x2x13 centrifugal 300 gpm/300 psi Centerline piston 150 gpm/600 psi

Air Compressor

Vanair/Sullair 900 cfm / 350 psi

Line Oiler

Many oilers available

Derrick slide/ dump

4' Derrick slide for angles up to 45°

Main Winch

Manual jib 2,500 lb. Remote on helpers side for winch

Control Panel

Straight hydraulic controls (no electrics to fail) Marine grade electric switches (for lights) Murphy engine monitor display Twin platforms

Levelling Jacks

Four 36" stroke independently controlled

Night Lights

6 LED night lights

Tool Boxes

30"x 18" x 18"

Overall Dimensions

Length: 24'11" Width: 8' 6"

Derrick up height: 24' 6" – 28' 6" with Derrick slide Derrick down height: 11'

Water Injection

9 gpm FMC injection pump

Gross Weight

36,000-38,000 lbs

Water Injection

18 gpm FMC injection pump

Drill pipe packages

Wire feeder and box

Hydraulic or gas welders



1018 7th street S.W. High River, AB, T1V 1A9 Canada 1 (403) 652-8778 sales@derex.ca www.derex.ca